



Product Data Sheet
CLEAR WATER RESIN
CONCRETE CURING COMPOUND
Revision: 001

DESCRIPTION

CLEAR WATER RESIN Concrete Curing Compound is a membrane forming treatment utilizing a dissipating hydrocarbon resin base combined in a treated clear water solution. This environmentally friendly V.O.C. compliant compound is designed to provide maximum curing to freshly-laid exterior concrete paving applications.

- V.O.C. compliant with maximum 350g/l content
- Excellent for subsequent flooring treatments
- Will not clog or plug spray equipment
- Provided in a ready-to-use formula

SPECIFICATIONS

- ASTM-C 309, Type I, Class B
- AASHTO M148, Type I, Class B

USE AND APPLICATIONS

CLEAR WATER RESIN Concrete Curing Compound is suitable for use with a wide variety of concrete construction projects. It is also ideal for many sizes of interior/exterior concrete slab work, as well as other flatwork applications.

- Roadways
- Airport Runways
- Parking Lots
- Curbs

FEATURES AND BENEFITS

Membrane forming treatment enhances slab water retention. Densifies and hardens concrete, reducing any crazing, cracking or checking. Tensile and compressive strengths are improved over non-cured slabs.

Packaging stable with no hard settlement

Coverage Rates

	Square Foot Per Gallon
Approximate	200

PACKAGING

- 5 gallon pails
- 55 gallon drums
- 275 gallon Tote

Drying Time:

1 hour maximum dependent on weather conditions and coverage rate. Will accept pedestrian foot traffic after 4 hour minimum.

APPLICATION PROCEDURES

- Incompatible with solvent containing products
- Ready to use formulation – no dilution required
- Aggressive mixing is not required and will result in excess foaming and stripping
- Spray evenly in a one coat application after the surface is free of all bleed water
- Use a spray rate of approximately ½ gallon per minute not exceeding 45 psi of pressure with any conventional piece of spray equipment.
- Clean up is accomplished with warm soapy water.

RESTRICTIONS:

Flash point: exceeds 212°F

Ready to use – DO NOT THIN

Do not contaminate with solvents

Water-based. Do not allow to freeze.

Use only when concrete temperature exceeds 40°F for 24 hours.

The Material Safety Data Sheet refers to additional health and safety information.

TECHNICAL SERVICE

For conditions not specified, application procedures not noted, contact: **Right Pointe Company (888) 755-5700**

LIMITED WARRANTY

Every reasonable effort is made to apply RIGHT POINTE COMPANY exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RIGHT POINTE COMPANY MAKE NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and RIGHT POINTE COMPANY shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the RIGHT POINTE COMPANY Technical Manager.