



PRODUCT SUBMITTAL

2000 Corrugated Wall Tie

WIRE-BOND



MATERIAL CONFORMANCE

SHEET METAL - (Carbon Steel) ASTM A1008 / A1008M

Mill Galvanized / Zinc Coating: ASTM A641 / A641M (0.10 Oz per sq ft)

Hot Dip Galvanized after fabrication / Zinc Coating
ASTM A153 / A153M-B2 (1.50 oz per sq ft)

Stainless Steel ASTM 580 / ASTM 580M Type 304 (Type 316 available on special order)

Steel Products (flats):

Mill Galvanized & Hot Dip,
61% Post-Consumer
9% Post Industrial / Pre -
Consumer

Stainless Steel,
60% Post Consumer
V O C Content - 0%

SIZES / FINISHES

2000 Corrugated Wall Tie:

16 gauge 22 gauge

Standard Size:

7/8" wide x 7" long

Custom sizes available

FINISH:

Mill Galvanized
 Hot Dip Galvanized
 Stainless Steel



Corporate Office: 400 Roundtree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113